



PERFORMANCE SERIES 7600 THINLINE WATER MANAGEMENT SILL MULTI-SLIDE DOOR

PRODUCT DATA SHEET



FOR MORE
CAD DETAILS
SCAN HERE



Performance Series 7600 Multi-Slide Door With Thinline Water Management Sill

The Series 7600 Thinline Water Management Multi-Slide Door features large, unobstructed rolling glass panels that stack flush to create extra-wide openings with seamless flooring transitions to connect indoor-outdoor commercial and living spaces. And even with extreme panel sizes, it is easy to operate, thanks to high-performance sealed bearing polymer rollers. The aluminum frame's clean lines, narrow profile, and high-quality anodized or painted finishes deliver a contemporary aesthetic that seamlessly blends into nearly any space, while managing water penetration through an innovative hidden subfloor drain system.

Energy Efficiency

- Low-E, argon-filled dual-paned, triple-paned glass
- .30 U-value

Hardware

- 1.81" roller
- Quad-Zilla roller
- Thinline sill
- Water barrier sill
- Flush sill
- Water management sill
- Flush-mounted handle
- Premium handle
- Contemporary handle
- Concealed locking system

Options

Handle options include a flush-mounted handle, which allows panels to slide past each other and stack flush. The contemporary handle features a minimal one-piece design and comfortable grip. Both handles have an optional keyed cylinder.

Finishes and Colors

Finishes are available in-stock or as designer selections, and they can be customized to match nearly any color. Split finishes are available in many combinations. Bronze Anodized and Satin Anodized come standard with a Class 1 coating thickness for increased smoothness and durability. Our designer colors include a high-quality paint finish that conforms to a minimum rating of AAMA-2605, currently the highest rating for organic finishes.

Performance Table

Frame Depth	2.87" Per Track
AAMA Product Designation (AAMA/WDMA/CSA101/I.S.2/A440 Designation)	CW-PG50 - 108" x 84"- SD
Test Configuration	108" x 84" XXO
Air Infiltration (Per ASTM E 283)	0.06 cfm/sf @1.57 psf
CSA A440 Air	N/A
Water Resistance (Per ASTM E 547)	9.0 psf
Uniform Load Deflection (Per ASTM E 330)	50 psf
Uniform Load Structural (Per ASTM E 330)	75 psf
Forced Entry Resistance	ASTM F842 Type B Grade 10
U-Factor (Per NFRC 100)*	0.30
CR (Per NFRC 500)*	57
CRF Frame (Per AAMA 1503)	69

Actual values may vary depending on product specifications and configuration.

* Glass Makeup = 1" OA E366/Argon/Clear





PERFORMANCE SERIES 7600 THINLINE WATER MANAGEMENT SILL MULTI-SLIDE DOOR

PRODUCT DATA SHEET



FOR MORE
CAD DETAILS
SCAN HERE



Threshold Condition At Track Clamps





PERFORMANCE SERIES 7600 THINLINE WATER MANAGEMENT SILL MULTI-SLIDE DOOR

PRODUCT DATA SHEET



FOR MORE
CAD DETAILS
SCAN HERE



Threshold Condition At Drain Block




PERFORMANCE SERIES 7600 THINLINE WATER MANAGEMENT SILL MULTI-SLIDE DOOR


PRODUCT DATA SHEET



FOR MORE
CAD DETAILS
SCAN HERE



Head Condition



Threshold Condition




PERFORMANCE SERIES 7600 THINLINE WATER MANAGEMENT SILL MULTI-SLIDE DOOR


PRODUCT DATA SHEET




FOR MORE
CAD DETAILS
SCAN HERE




Left Jamb Condition



Right Jamb Condition



Interlocking Condition



Full Jamb Condition TYP




PERFORMANCE SERIES 7600 THINLINE WATER MANAGEMENT SILL MULTI-SLIDE DOOR

PRODUCT DATA SHEET



FOR MORE
CAD DETAILS
SCAN HERE



Horizontal Section Of
3-Panel Stacking Door Or 2XO




PERFORMANCE SERIES 7600 THINLINE WATER MANAGEMENT SILL MULTI-SLIDE DOOR

PRODUCT DATA SHEET



FOR MORE
CAD DETAILS
SCAN HERE



1" Stucco Return Wall Construction Profile At Stud
Multi-Slide Door Jamb Application




PERFORMANCE SERIES 7600 THINLINE WATER MANAGEMENT SILL MULTI-SLIDE DOOR

PRODUCT DATA SHEET



FOR MORE
CAD DETAILS
SCAN HERE



1.375" Stucco Return Wall Construction Profile At Stud
Multi-Slide Door Jamb Application